

AquFlow

S2000 PERFORMANCE TABLE

Model No.	Capacity GPH (LPH)	Pressure PSIG (bars)	Speed (SPM)	Plunger Diameter	Connection (NPT)
CD3T 0529-0X14	2.95 (11.2)	1,800 (124)	29	5/8"	3/8"
CD3T 0558-0X14	5.90 (22.3)	1,800 (124)	58	5/8"	3/8"
CD3T 0597-0X14	9.90 (37.5)	1,800 (124)	97	5/8"	3/8"
CD3T 0512-0X14	11.9 (45.0)	1,800 (124)	117	5/8"	3/8"
CD3T 0514-0X14	14.3 (54.1)	1,800 (124)	140	5/8"	3/8"
CD3T 0519-0X14	19.5 (73.8)	1,800 (124)	191	5/8"	3/8"
CD3T 0629-0X14	4.25 (16.0)	1,000 (69)	29	3/4"	3/8"
CD3T 0658-0X14	8.55 (32.4)	1,000 (69)	58	3/4"	3/8"
CD3T 0697-0X14	14.3 (54.1)	1,000 (69)	97	3/4"	3/8"
CD3T 0612-0X14	17.2 (65.1)	1,000 (69)	117	3/4"	3/8"
CD3T 0614-0X14	20.6 (78.0)	1,000 (69)	140	3/4"	3/8"
CD3T 0619-0X14	28.1 (106.4)	1,000 (69)	191	3/4"	3/8"
CD3T 0829-0X14	7.60 (28.8)	360 (25)	29	1"	3/8"
CD3T 0858-0X14	15.2 (57.5)	361 (25)	58	1"	3/8"
CD3T 0897-0X14	25.4 (96.1)	362 (25)	97	1"	3/8"
CD3T 0812-0X15	30.6 (115.8)	363 (25)	117	1"	1/2"
CD3T 0814-0X15	36.7 (138.9)	364 (25)	140	1"	1/2"
CD3T 0819-0X15	50.0 (189.3)	365 (25)	191	1"	1/2"
CD3T 1029-0X14	11.8 (44.7)	210 (14)	29	1-1/4"	3/8"
CD3T 1058-0X14	23.7 (89.7)	210 (14)	58	1-1/4"	3/8"
CD3T 1097-0X18	39.7 (150.3)	210 (14)	97	1-1/4"	1/2"
CD3T 1012-0X18	47.9 (188.1)	210 (14)	117	1-1/4"	1/2"
CD3T 1014-0X18	57.3 (216.9)	210 (14)	140	1-1/4"	1/2"
CD3T 1019-0X18	78.2 (296.0)	210 (14)	191	1-1/4"	1/2"
CD3T 1229-0X14	17.1 (64.7)	195 (13)	29	1-1/2"	3/8"
CD3T 1258-0X15	34.2 (129.5)	195 (13)	58	1-1/2"	1/2"
CD3T 1297-0X18	57.2 (216.5)	195 (13)	97	1-1/2"	1/2"
CD3T 1212-0X18	69.0 (261.2)	195 (13)	117	1-1/2"	1/2"
CD3T 1214-0X18	82.5 (312.3)	195 (13)	140	1-1/2"	1/2"
CD3T 1219-0X18	112.0 (424.0)	195 (13)	191	1-1/2"	1/2"

